

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

**Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:**

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH | Tel. **+49 - 81 41 - 52 71-0**
Am Sonnenlicht 2 | Fax **+49 - 81 41 - 52 71-129**
82239 Alling/Germany | E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.


www.meilhaus.de

High Power Attenuator



Product Overview

This series high power attenuator coaxial load adopts the aluminium nitride resistor and lead-free technique. Its connector conforms to the MIL-C-39012 standard. This product features high precision and long service life; and is innocuous and environment-friendly.



This attenuator can be used in various tests and terminal matching; for example, the test adjustment of power amplifier as well as the splitter and coupling terminals matching.

Note: This product should be protected from rain. The radiating fin should be installed vertically. Good ventilation should be ensured for the radiator.

Specifications

Modle	ATT03301H
Quantity	1
Impedance	50 Ω
Frequency Range	DC to 3 GHz
Max. VSWR	1.25
Power	100 W
Temperature range	-55°C to +125°C
Attenuation	30 dB
Insertion Loss	± 1 dB