

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

**Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:**

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH | Tel. **+49 - 81 41 - 52 71-0**
Am Sonnenlicht 2 | Fax **+49 - 81 41 - 52 71-129**
82239 Alling/Germany | E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.

www.meilhaus.de

4051-S Series Signal/Spectrum Analyzers support incomparable spectrum measurement services of high price-performance ratio. The analyzers have excellent dynamic range, phase noise, amplitude precision and measurement speed, can supply ten measurement functions in total including high-performance spectrum analysis, standard power measurement modules conforming to relevant criteria etc. Capabilities of the analyzers can be greatly augmented. Multiple practical options are available like preamplifier, phase noise measurement, random IF output and so on. 4051 Series can be widely applied in signal and instrument tests relating to fields of aerospace, communication, EMC, radar detection, navigation, etc.

- Convenient Operation Characteristics
- Incomparable Price-Performance Ratio
- 5 Frequency Range, Up to 26.5GHz
- Excellent Measurement and Receiving Performance
- Overall spectrum analysis capability
- Practical Function Options

Convenient Operation Characteristics

- Chinese/English are available
- Humanized automatic tuning and automatic scale
- One-button measurement
- 10.1 inch LCD, 1280*800 screen resolution, display more clear measurement results
- Support USB, LAN, GPIB, monitor etc., for your convenience.

Incomparable Price-Performance Ratio

- Economy price effectively reduce testing cost
- Offer outstanding performance and specifications which can only be provided by high end analyzers


5 Frequency Range, up to 26.5GHz

- The max. coaxial frequency range of 26.5GHz
- 5 frequency ranges available, you can choose based on budgets
- Can supply broadband preamplifiers to match different frequency range

Main Characteristics

Excellent Measurement & Receiving Performance


- 1GHz testing DANL is -153dBm/Hz. If configured with preamplifier, the typical value is -166dBm/Hz.
- 26.5GHz testing DANL is -141 dBm/Hz, configured with preamplifier, the typical value is -160dBm/Hz.
- All digital IF design, fine scale fidelity and IF error rate.



Main Characteristics

Overall Spectrum Analysis Capabilities


- Support frequency sweep and FFT sweep.
- Zero frequency band fast sweep, the fastest sweep time is 1 μ s
- Accurate frequency counting, counting resolution can be 0.001Hz
- Sweep point number can be arbitrarily selected among 101 ~ 30001
- 6 traces can be configured, with abundant marker operation functions
- 6 trace detector modes, 3 average types
- Support time gate measurement
- Occupied bandwidth, channel power, adjacent channel power measurement functions
- Measurement functions of power statistics, burst power, harmonic distortion, TOI, spurious emission etc.



Main Characteristics

Practical Function Options

- Phase noise testing capability
- RF or full band preamplifiers
- 10MHz~160MHz random IF output, 1Hz steps, 4 auto gain control levels



- RF performance assessment of electronic systems

as universal spectrum analyzers of multiple functions, 4051-S Series Signal/Spectrum analyzers can be widely used in RF performance evaluative of electronic systems in fields like radar, communication and so on. They can provide high sensitivity, wide dynamic range, and high precision and efficiency resolutions.

- Measurement and diagnosis of transmitter and receiver

4051-S Series can furnish comprehensive common diagnosis services for transmitter and receiver by the multiple functions of spectrum analysis, spectral power testing, and phase noise Measurement and so on.

- Can be directly used for the integration of complex test and diagnosis systems, to get test results of spectrum characteristics and signal output.

Technical Specifications

	Model	DC coupled	AC coupled
Frequency range	4051A-S	3Hz~4GHz	10MHz~4GHz
	4051B-S	3Hz~9GHz	10MHz~9GHz
	4051C-S	3Hz~13.2GHz	10MHz~13.2GHz
	4051D-S	3Hz~18GHz	10MHz~18GHz
	4051E-S	3Hz~26.5GHz	10MHz~26.5GHz
10MHz Precise frequency reference	Frequency accuracy: \pm (last calibration date x aging rate + temperature stability + calibration accuracy) Aging rate: $\pm 1 \times 10^{-7}$ /year Temperature stability: $\pm 1.5 \times 10^{-8}$ (20°C ~ 30°C) $\pm 5 \times 10^{-8}$ (0°C ~ 55°C) ($\pm 1.5 \times 10^{-8}$) Calibration accuracy: $\pm 4 \times 10^{-8}$		
Frequency readout accuracy	\pm (frequency readout x frequency reference accuracy + 0.1% frequency band + 5% resolution bandwidth + 2Hz + 0.5 horizontal resolution*) *: horizontal resolution = span / (sweep points number - 1)		
Frequency counting accuracy	\pm (frequency readout x frequency reference accuracy + 0.1Hz)		
Span	Range: 0Hz (zero span), 10Hz~the highest frequency of the model Accuracy: \pm (0.1% x span + span / (sweep points number - 1))		
Sweep time range	span \geq 10Hz: 1ms~6000s span = 0Hz: 1us~6000s		
Resolution bandwidth	Range: 1Hz~3MHz (1, 2, 3, 5 steps) 4, 5, 6, 8, 10, 20MHz Conversion uncertainty: ± 0.3 dB 1Hz~10MHz ± 1.0 dB 20MHz		
Video bandwidth	1Hz~3MHz (1, 2, 3, 5 steps) 4, 5, 6, 8, 10, 20MHz (rated value)		
Trigger source	Free, Line, video, external level (front panel), external level (back panel), burst RF, timer		
Trace detector	Normal, positive peak, negative peak, sample, video average, power average, voltage average		
Average Mode	Video Average, power average, level average		
SSB Phase Noise (1GHz Carrier) 20°C ~ 30°C	-92dBc/Hz 100Hz -105dBc/Hz 1kHz -118dBc/Hz 10kHz -123dBc/Hz 100kHz		
Residual FM (Central Frequency 1GHz, Resolution Bandwidth 10Hz, Video Bandwidth 10 Hz)	\leq (0.25 Hz x N) p-p, nominal value within 20 ms N is frequency multiplication times of LO		
Displayed Average Noise Level (the Input End is Connected to Match Load, Sampling or Average Wave Detection. The Average Type is Lo- garithm, OdB Input Attenuation, RF Gain Takes the DANL as the Priority, 20°C ~ 30°C)	-153dBm 10MHz~1GHz -151dBm 1GHz~2GHz -150dBm 2GHz~3GHz -148dBm 3GHz~3.6GHz -145dBm 3.6GHz~4GHz -148dBm 4GHz~5GHz -150dBm 5GHz~9GHz -146dBm 9GHz~18GHz -141dBm 18GHz~26.5GHz		

Technical Specifications

Frequency Response & Absolute Amplitude Accuracy (10dB Attenuation, 20°C ~ 30°C)	<p>Frequency response:</p> <p>±1.0dB 3Hz~20MHz ±1.0dB 20MHz~2GHz ±1.0dB 2Hz~3.6GHz ±1.2dB 3.6GHz~4GHz ±1.5dB 4GHz~9GHz ±2.0dB 9GHz~18GHz ±3.0dB 18GHz~26.5GHz</p> <p>Absolute amplitude accuracy 10 dB Attenuation, 20°C ~ 30°C, 1 Hz ≤ Resolution bandwidth ≤ 1 MHz, Input signal-10 ~ -50 dBm):</p> <p>±0.24dB 500MHz ±(0.24dB+Frequency response) All frequencies</p>
1dB gain Compression (Mixer Level, Dual-Tone Testing, Resolution Bandwidth of 5kHz, Frequency Interval of 3MHz, 20°C ~ 30°C)	<p>-3dBm 20MHz~40MHz 0dBm 40MHz~200MHz +1dBm 200MHz~4GHz -1dBm 4GHz~9GHz</p>
TOI (Input mixer 2 -10dBm signals, Frequency Interval is 50kHz, 20°C~30°C)	<p>+12dBm 10MHz ~ 200MHz +12dBm 200MHz ~ 4GHz +10dBm 4GHz ~ 9GHz +12dBm 9GHz ~ 18GHz +13dBm 18GHz ~ 26.5GHz</p>
Residual Response (The Input End is Connected to Match Load, 0dB Attenuation)	<p>-100dBm 200kHz~9GHz -100dBm (nominal) Other frequencies</p>
Size	<p>W×H×D= 510mm×192mm×534mm (with handles, foot-pads, stand) W×H×D= 426mm×177mm×460mm (without handles, foot-pads, stand)</p>
Weight	Approx. 25kg (different options, different weight)
Power	<p>Standard: AC 220~240V: 50~60Hz 4051-H98: AC 100~240V: 50~60Hz</p>
Power Consumption	Standby: less than 20W; operating: less than 400W
Temperature Range	Operating temperature: 0°C ~ +50°C ; Storage temperature: -40°C ~ +70°C
Input Connector	<p>4051A-S/4051B-S/4051C-S/4051D-S: type N (F) Impedance 50Ω 4051E-S: 3.5mm (M), Impedance 50Ω</p>

Notes:

1. Nominal value refers to the estimated performance, or the performance which is useful for the product beyond the quality guarantee scope.
2. Typical value refers to other performance information when typical values stay beyond the quality guarantee scope. When performance surpasses technical specifications, 80% of samples will present 95% confidence within 20°C ~ 30°C temperature range. Typical performance excludes test uncertainty.

Main unit: 4051A-S signal/spectrum analyzer (3Hz~4GHz)

Main unit: 4051B-S signal/spectrum analyzer (3Hz~9GHz)

Main unit: 4051C-S signal/spectrum analyzer (3Hz~13.2GHz)

Main unit: 4051D-S signal/spectrum analyzer (3Hz~18GHz)

Main unit: 4051E-S signal/spectrum analyzer (3Hz~26.5GHz)

Standard Package

No.	Description	Remarks
1	Power cord	Standard tri-prong power cord
2	USB mouse	-
3	User manual	-
4	Programming manual	-

Options

No.	Description	Function
4051-H03	IF Output	Output third IF signal, output frequency range is 10MHz ~ 160MHz, step resolution is 1Hz.
4051-H08	Wide Log Detect Output	To output the logarithm wave-detection signal which can reflect the input signal level characteristics.
4051-H34-04 4051-H34-09 4051-H34-13 4051-H34-18 4051-H34-26	Low-Noise Preamplicifier	Can select low waveband preamplicifier or full waveband preamplicifier. Under full waveband preamplicifier, the analyzer provide above 4GHz frequency band noise optimization path. (Note: the No. of low waveband preamplicifier is H34-04. The full waveband preamplicifier should be selected according to the frequency upper limit of the main unit. For instance, the max. frequency of 4051E-S is 26.5GHz, then the full waveband preamplicifier H34-26 should be selected).
4051-S04	Phase Noise Measurement	SSB phase noise curves and single-point phase noise measurement.
4051-H97	Mounting Suit	Handles and accessories for 4051 mounting on standard racks.
4051-H98	English Options	English panels, user manual, operation interface, and operation system. Power supply: AC 100~240V: 50~60Hz.
4051-H99	Aluminum Transportation Case	High-strength lightweight aluminum transportation case, with handle and roller, convenient for transportation.