

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

FAX: **+49 - (0)81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0**
Fax **+49 - (0)81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

FLIR ETS320™

Thermal Imaging Solution for Electronics Testing



The FLIR ETS320 is an affordable solution for reducing test times and improving product design for electronic board and device evaluation. Whether the goal is R&D or product testing, heat can be an important indicator of how a system is functioning. The ETS320 helps engineers and test technicians collect accurate, reliable data in seconds and analyze it quickly.

Reduce Test Times

The FLIR ETS320 takes the guesswork out of thermal testing, for fast discovery of hot spots and potential points of failure.

- Sensitive enough to detect temperature shifts smaller than 0.06°C
- Wide temperature range, from -20°C to 250°C, for quantifying heat generation and thermal dissipation
- Measures small components down to 170 µm per pixel spot size

Improve Product Design

The FLIR ETS320 promotes design improvements and shortens product development time by detecting design flaws that materialize as heat.

- 320 x 240 IR sensor offers 76,800 points of non-contact temperature measurement
- True 45° field of view for broad initial scans to identify potential problems
- Measurement accuracy of ±3°C promotes quality assurance and factory acceptance of PCBs


Designed for Laboratory Work

The ETS320 is designed for hands-free laboratory testing, with simplified features that allow users to focus on their work instead of on the camera controls.


- Pole mount included for fast and easy setup
- Crisp 3" LCD display provides immediate thermal feedback
- FLIR Tools+ software for instant analysis, including Time vs. Temperature measurement

Key Features:

- 320 x 240 IR resolution (76,800 pixels)
- Vibrant 3" LCD display
- 45° field of view
- ±3% measurement accuracy
- Records standard radiometric JPEGs
- FLIR Tools+ software provided



Measure small components down to 170 µm per pixel spot size



Determine where to add or remove thermal management devices



Connect over USB a computer to analyze data in FLIR Tools+

Specifications

System Overview		ETS320
IR Resolution		320 x 240 (76,800 pixels)
Detector Type		Uncooled microbolometer
Spectral Range		7.5 - 13.0 μm
Thermal Sensitivity/NETD		< 0.06°C
Field of View (FOV)		45° x 34°
Fixed Focus Distance		70 mm \pm 10 mm
F-number		1.5
Spot Size @ Min. Focus		170 μm
Image Frequency		9 Hz
Measurement and Analysis		
Object Temperature Range		-20°C to 250°C
Accuracy		\pm 3°C or \pm 3% of reading for ambient temperature 10°C to 35°C
Spotmeter		Center spot
Area		Box with max/min
Emissivity Correction		Variable from 0.1 to 1.0
Emissivity Table		Table of pre-defined materials
Reflected Apparent Temperature Correction		Automatic, based on input of reflected temperature
Storage of Images		
Image File Formats		Standard radiometric JPEG, 14-bit measurement data included
Video Streaming		
Radiometric IR Video Streaming		Full dynamic to PC (FLIR Tools/Tools+) using USB
Non-Radiometric IR Video Streaming		Uncompressed colorized video using USB
Data Communication Interfaces		
Interfaces		USB Micro: data transfer to and from PC and Mac devices
Power System		
Battery Type		Li-ion battery, charged in camera
Battery Operating Time		Approx. 4 hours at 25°C (77°F) ambient temperature and typical use
Charging Time		2.5 hrs to 90% capacity
Additional Data		
Display		3 in, 320 x 240 pixel color LCD
Operating Temperature Range		10°C to 40°C
Storage Temperature Range		-40°C to 70°C
Directives and Regulations		<ul style="list-style-type: none"> • Battery Directive 2006/66/EC • EMI/EMC Directive 2014/30/EU • WEEE Directive 2012/19/EC • RoHS2 Directive 2011/65/EC • FCC 47 CFR Part 15 Class B • REACH Regulation EC 1907/2006
Encapsulation, Shock, Vibration		• IP 40 (IEC 60529)
Camera Weight, Incl. Battery		575 g
Camera Size (L x W x H)		22 x 15 x 30 cm
FLIR ETS320 Includes:		
List of Contents		Camera, mount, stand, power supply, USB cable, FLIR Tools+ software

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 16-1715_EMEA



The World's Sixth Sense®