

Product Datasheet - Technical Specifications



More information in our Web-Shop at > www.meilhaus.com

Your contact

Technical and commercial sales, price information, quotations, demo/test equipment, consulting:

Tel.:	+49 - (0)81 41 - 52 71-0
FAX:	+49 - (0)81 41 - 52 71-129
E-Mail:	sales@meilhaus.com

Meilhaus Electronic GmbH Tel. Am Sonnenlicht 2 82239 Alling/Germany Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

+49 - (0)81 41 - 52 71-0 Fax +49 - (0)81 41 - 52 71-129 E-Mail sales@meilhaus.com

www.meilhaus.com



Universal Soft Sided Case

P/N: TA15

Copyright

© 2020, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: TA15 Commit: 64527 Language: en-US Modified: 2020-03-17 Formatted: 2020-03-18

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
Part number	TA15
Part name	Universal Soft Sided Case
FLIR clamp meter, flex clamp accessory, test	nent soft-sided case designed to protect and carry your t leads, or any other tool you need on the job. It is neter and the FLIR Universal Flex Current Probe ne).
Meter data	
Suitable main unit	Main compartment: CM174, CM74, CM72, CM85, CM83, CM82, CM78
	Secondary compartment: TA74, TA72, CM57, CM57
Warranty	https://www.flir.com/testwarranty
Meter physical data	
Weight	0.22 kg
Dimensions (H \times W \times L)	26.0 cm × 13.5 cm × 8.5 cm
Material	Black ballistic polyester (exterior), PEVA with velvet finish (interior), PET screen (ID slot)
Color	Black
Shipping information	
Packaging type	Colored box with view of product behind clear plastic cover
Packaging contents	Protective case, removable handle
Packaging weight	0.35 kg
Packaging dimensions (H \times W \times L)	32.7 cm × 7 cm × 13.7 cm
Carton weight	4.3 kg



Universal Soft Sided Case

P/N: TA15

© 2020, FLIR Systems, Inc. #TA15; r. 64527; en-US

Shipping information			
Carton dimensions ($H \times W \times L$)	15.5 cm × 40 cm × 60 cm		
Carton quantity	10		
EAN-13	0793950377154		
UPC-12	793950377154		
Country of origin	China		
Tariff code	4202122020		
Technical support			
Website	http://support.flir.com		

Compatible with the following products:

- CM174; FLIR CM174: Imaging 600A AC/DC Clamp Meter with IGM
- CM275; FLIR CM275: Industrial Thermal Imaging Clamp Meter with Datalogging, Wireless Connectivity, and IGM
- CM42; FLIR CM42: Professional 400A TRMS AC Clamp Meter
- CM44; FLIR CM44: Professional 400A TRMS AC Clamp Meter + Type K
- CM46; FLIR CM46: Professional 400A TRMS AC/DC Clamp Meter + Type K
- CM55; FLIR CM55: Flex Clamp Meter with Bluetooth
- CM57; FLIR CM57: Large Flex Clamp Meter with Bluetooth
- CM65; FLIR CM65: True RMS 600A Solar Clamp Meter with METERLINK
- CM72; FLIR CM72: Commercial 600A AC Clamp Meter
- CM74; FLIR CM74: Commercial 600A AC/DC Clamp Meter
- CM78; FLIR CM78: True RMS Clamp/DMM with infrared thermometer and Bluetooth METERLINK
- CM82; FLIR CM82: 600 Amp Power Clamp Meter with VFD Mode
- CM83; FLIR CM83: 600 A True RMS Power Clamp Meter
- CM85; FLIR CM85: 1000 Amp Power Clamp Meter with VFD Mode and METERLINK
- CM94; FLIR CM94: True RMS AC/DC 2000A Utility Clamp Meter with LoZ
- DM166; FLIR DM166: Thermal Imaging TRMS Multimeter with IGM
- DM284; FLIR DM284: Imaging Multimeter with IGM
- DM285; FLIR DM285: Industrial Thermal Imaging Multimeter with Datalogging, Wireless Connectivity, and IGM
- DM62; FLIR DM62: TRMS Digital Multimeter with Non-contact Voltage
- DM64; FLIR DM64: HVAC TRMS Digital Multimeter with Temperature
- DM66; FLIR DM66: Electrical and Field Service TRMS Multimeter with VFD Mode
- DM90; FLIR DM90
- DM91; FLIR DM91: Industrial TRMS Multimeter with Datalogging and Wireless
 Connectivity
- DM92; FLIR DM92: Industrial Digital Multimeter with LoZ and VFD Mode
- DM93; FLIR DM93: True RMS Industrial Multimeter
- IM75; FLIR IM75: Insulation Tester and Digital MultiMeter with VFD Mode and METERLINK
- VT8-1000; FLIR VT8-1000: Voltage, Continuity and Current Tester
- VT8-600; FLIR VT8-600: Voltage, Continuity and Current Tester