

## Product Datasheet - Technical Specifications



More information in our Web-Shop at ► [www.meilhaus.com](http://www.meilhaus.com)

### Your contact

Technical and commercial sales, price information,  
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

E-Mail: [sales@meilhaus.com](mailto:sales@meilhaus.com)

**Meilhaus Electronic GmbH**  
Am Sonnenlicht 2  
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0** E-  
Mail [sales@meilhaus.com](mailto:sales@meilhaus.com)

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

**[www.meilhaus.com](http://www.meilhaus.com)**

# LH35 3.0

## Thermal Monocular



With a basic magnification of 3.4x, a 384x288 detector, and a 35mm F1.0 lens, the LH35 3.0 offers unparalleled performance for professional hunters and mid-to-long-range applications. Its 7.5° (13.1m at 100m) field of view and a detection range of up to 1800m ensure exceptional detail in vast, open spaces, making it the ultimate choice for serious users seeking premium quality with proven shutterless technology.

### Key Feature

- High-sensitivity thermal module with NETD < 15 mK
- 35 mm, F1.0 lens with thermal detection range up to 1800 m
- AI-powered Image Pro 3.0 and Zoom Pro algorithms
- HIKMICRO Shutterless Image System (HSIS)
- 0.49-inch 1920 × 1080 resolution AMOLED display
- Replaceable and rechargeable 18650 battery provides up to 4.5 hours of continuous operation at -20°C
- Lightweight design at 354.5g, with a pocket-sized build

# Specification


| Thermal Module                           |                                                                         |
|------------------------------------------|-------------------------------------------------------------------------|
| Image Sensor                             | VOx Uncooled Focal Plane Arrays                                         |
| Max. Resolution                          | 384 × 288                                                               |
| Frame Rate                               | 50 Hz                                                                   |
| Pixel Interval                           | 12 μm                                                                   |
| Response Waveband                        | 8 μm to 14 μm                                                           |
| NETD                                     | Less than 15 mK (@25°C), F#=1.0                                         |
| Lens (Focal Length)                      | 35 mm, F1.0                                                             |
| Focus Mode                               | Focus Wheel                                                             |
| Min. Focusing Distance                   | 3.5 m                                                                   |
| Magnification                            | 3.4 × - 27.2 × (8 ×)                                                    |
| Field of View(H × V), Degrees / m @100 m | 7.5° × 4.6°/13.1 m × 8.0 m                                              |
| Detection Range                          | 1800 m                                                                  |
| Image Display                            |                                                                         |
| Display                                  | 1920 × 1080, 0.49 inch, AMOLED                                          |
| Contrast Adjustment                      | Yes                                                                     |
| Brightness Adjustment                    | Yes                                                                     |
| Palettes                                 | Black Hot, White Hot, Red Hot, Fusion, Red Monochrome, Green Monochrome |
| Exit Pupil                               | 6 mm                                                                    |
| Eye Relief                               | 20 mm                                                                   |
| Diopter (Range)                          | -5 D to +3 D                                                            |
| Tone Adjustment                          | Cold, warm                                                              |
| Zoom Pro                                 | Yes                                                                     |
| HSIS (HIKMICRO Shutterless Image System) | Yes                                                                     |
| Image Pro 3.0                            | Yes                                                                     |
| Sync Pro                                 | Yes                                                                     |
| System                                   |                                                                         |
| Storage                                  | Built-in EMMC (64GB)                                                    |
| Record Video                             | Yes                                                                     |
| Capture Snapshot                         | Yes                                                                     |
| Local Album                              | Yes                                                                     |
| Standby Mode                             | Yes                                                                     |
| PIP                                      | Yes                                                                     |
| Hotspot                                  | 2.4/5 G WiFi Waveband                                                   |
| Hot Track                                | Yes                                                                     |
| Distance Measurement                     | Yes                                                                     |
| Audio Recording                          | Yes                                                                     |

| Power Supply              |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Battery Type              | Replaceable and rechargeable 18650 battery                             |
| Battery Operating Time    | ≥5h (@25°C, WiFi on)<br>≥4.5h (@-20°C, WiFi on)                        |
| Type-C Power Supply       | 5 V DC, 2 A<br>Supports External Power Supply, Support Direct Charging |
| General                   |                                                                        |
| Work Temperature/Humidity | From -30°C to 45°C (-22°F to 113°F); Humidity: 90% or Less             |
| Protection Level          | IP67                                                                   |
| Dimension                 | 169.6 x 53.6 x 49.5 mm                                                 |
| Weight                    | 354.5 g with Battery                                                   |

Available Model

HM-TSF3-35Y1G/W1-LH35 3.0

Dimension



Unit: mm [Inch]

## Accessories



Battery Charger (×1)



Battery (×2)



Lint-Free Cloth (×1)



Type-C Cable (×1)



Quick Start Guide(×1)

COMPLIANCE NOTICE: The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries.