

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH | Tel. **+49 - 81 41 - 52 71-0**
Am Sonnenlicht 2 | Fax **+49 - 81 41 - 52 71-129**
82239 Alling/Germany | E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.

Maverick™ 63104

DisplayPort 1.2a and USB 3.1, 5Gbps Point-to-Point Extender System over CAT 6a/7

Industry's first DisplayPort 4Kp60 and USB 3-2-1 Extender over a single CAT 6a/7 cable up to 100m

The DisplayPort 1.2a 4Kp60 4:4:4 and USB 3.1 Gen 1 Maverick™ 63104 provides the ability to connect all USB device types and a single DisplayPort sink back to a host across a point-to-point connection up to 100m over CAT 6a/7. The Maverick 63104 also includes an Ethernet pass-through for connecting to network enabled devices or to use existing infrastructure without losing LAN connectivity, as well as an RS232 pass-through channel for command and control applications or RS232 enabled devices.



Local Extender

Remote Extender

Summary of Features


- DisplayPort 1.2a with embedded audio support
- Resolutions up to UHD 4K, 3840 x 2160 @60Hz
- YCbCr 4:4:4 and RGB colour support up to 10bpc
- 2 Channel DisplayPort Audio
- USB 3.1 Gen 1 data rate up to 5Gbps
- Supports all USB 3.1, 2.0, 1.1 devices simultaneously at full bandwidth
- Four available 3.1 Gen 1 ports
- 100/1000 Ethernet channel; LAN pass-through
- Bidirectional RS232, 9600-115200 baud rate
- Single cable, CAT 6a/7 up to 100m
- Point-to-point connection

Includes the ExtremeUSB-C™ suite of features:


- Transparent USB extension supporting USB 3, 2 and 1
- True plug and play; no software drivers required
- Works with all major operating systems: Windows®, macOS™, Linux® and ChromeOS™

Applications

- Medical Imaging
- Video Production
- Interactive Digital Signage
- Industrial Control/HMI



Maverick 63104 Specifications

LOCAL EXTENDER MECHANICAL DATA		REMOTE EXTENDER MECHANICAL DATA			
137.3mm x 232.1mm x 33.0mm (5.4" x 9.1" x 1.3")		137.3mm x 232.1mm x 33.0mm (5.4" x 9.1" x 1.3")			
1x USB 3.1 B Receptacle		4x USB 3.1 A Receptacles			
1x RJ45 Ethernet 100/1000 Port		1x RJ45 Ethernet 100/1000 Port			
1x DisplayPort 1.2a Receptacle		1x DisplayPort 1.2a Receptacle			
1x RS232 3-Pin Terminal Block		1x RS232 3-Pin Terminal Block			
1x RJ45 Ethernet Link Port		1x RJ45 Ethernet Link Port			
24V 1A DC Locking Jack		24V 2.71A DC Locking Jack			
920g (2.03 lbs.)		990g (2.18 lbs.)			
PACKAGE CONTENTS					
1x Local Extender					
1x Remote Extender					
2x 1.8m DisplayPort Cables					
1x 1.8m USB 3.1 Gen 1 Cable					
2x International Locking Power Adapters					
2x Country Specific Power Cords					
1x Quick Start Guide					
Packaged weight: 2.95kg (6.49 lbs.)					
RANGE					
Point-to-Point:	Up to 100m over CAT 6a/7				
USB SUPPORT					
USB Speeds:	SuperSpeed 5Gbps, High-Speed, Full-Speed, Low-Speed				
USB Bandwidth:	Up to 5Gbps				
Device Compatibility:	All Device Types and Classes (Control, Interrupt, Isochronous and Bulk)				
Host Compatibility:	OHCI, UHCI, EHCI, xHCI				
Available Current at Remote:	1.2A (6W) per USB port				
Max Number of USB Devices:	30				
ENVIRONMENTAL					
Temperature:	0°C – 50°C (32°F – 122°F) Operating, -20°C – 70°C (-4°F – 158°F) Storage				
Humidity:	20-80% Operating, 10-90% Storage Relative Humidity Non-Condensing				
SUPPORT					
Warranty:	2 years				

Ordering Information

PART #	NAME	DESCRIPTION
01-00633	Maverick 63104 - EU	4-Port USB 3-2-1 and DisplayPort 4Kp60 4:4:4 CAT 6a/7 100m Extender System, Unbranded Black, 24V 100-240V Power Adapters - EU