

## Product Datasheet - Technical Specifications



More information in our Web-Shop at ► [www.meilhaus.com](http://www.meilhaus.com)

### Your contact

Technical and commercial sales, price information,  
quotations, demo/test equipment, consulting:

Tel.: +49 - (0)81 41 - 52 71-0

E-Mail: [sales@meilhaus.com](mailto:sales@meilhaus.com)

**Meilhaus Electronic GmbH**  
Am Sonnenlicht 2  
82239 Alling/Germany

Tel. +49 - (0)81 41 - 52 71-0 E-  
Mail [sales@meilhaus.com](mailto:sales@meilhaus.com)

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

## Managed Switch PROmesh B8 compact

### PROmesh B8 compact



Art.-Nr.: 114110520

### HIGHLIGHTS



8 RJ45 Ports

#### Design Data Engineering:

- E-Plan | Step
- GSDML (PROFINET)
- EDS (Ethernet/IP)



#### Industry Applications:

- PROFINET
- Ethernet/IP



#### Country approvals:

- UL | CSA
- CE | UKCA



#### Performance:

- Memory: 2 Mbit
- Backplan capacity: 6,3 Gbit/s
- Throughput: 1,6 Mpps

#### Sustainability:

- Lead-free
- Lowpower consumption

## Managed Switch PROmesh B8 compact

### Technical details

Network interfaces	
RJ45 Ports	
■ Interfaces	8
■ Transmission rates	10 Mbit/s 100 Mbit/s
■ Status LED	Link + Datacommunication
Supply voltage, current consumption, power dissipation, alarm contact	
Connections	
■ Power supply	2 x 0,2 – 2,5 mm <sup>2</sup>
■ functional earthing	1 x 0,2 – 2,5 mm <sup>2</sup>
Operating parameters	
■ Supply voltage (nominal value)	24 VDC
■ Supply voltage (min.)	12 VDC
■ Supply voltage (max.)	36 VDC
Environmental conditions	
■ Operating temperature	-10°C ... 60°C
■ Storage temperature	-10°C ... 60°C
■ Humidity, rel.	<95% RHD, non-condensing
■ protection level	IP20
Design, dimensions, weights	
■ Design	compact, passive cooling
■ Material (housing)	sheet metal bending housing, painted
■ Mounting	35 mm DIN rail (0°, 90°)
■ Weight	350 g
■ Width	50 mm
■ Height	100 mm
■ Depth	60 mm
■ Mounting distance (vertical)	50 mm
■ Mounting distance (horizontal)	20 mm
Further device interfaces	
■ Status LED	VDC1 Status Error Port LED
■ Reset	Button
■ SD Card Storage	yes
Functions	
Basic parameters	
■ Switching Technologie	Store & Forward
■ MAC address table	16 K
■ Packet memory	2 Mbit
■ Backplane capacity	6,3 Gbit/s
■ Throughput	1,6 Mpps

## Managed Switch PROmesh B8 compact

### Technical details

Functions	
Quality of Service (QoS)	
■ Queues pro Port	8
■ Prioritization methods	Strict prioritization Weighted prioritization
■ Bandwidth control	inbound and outbound
■ Port prioritization	yes
■ COS: Class of Service	yes
■ TOS: Type of Service	yes
VLAN	
■ Log function	yes
■ Tagged	yes
■ Quantity	4096
Protocols/Services	
■ Management access	HTTP HTTPS Webmanagement PROmanage NT
■ Network	SNMPv1 SNMPv2c SNMPv3
■ Time synchronization	SNTP Client
■ Neighborhood	LLDP
■ Multicast Groups	Static Multicast IGMP Snooping Broadcast limitation
■ Redundancy	MRP Master MRP Client STP RSTP
■ Event log	Syslog
■ IP Setting	Static PROFINET ETHERNET/IP
■ Multicast/Broadcast	Static Multicast IGMP Snooping Broadcast limitation
Application-specific	
PROFINET	
■ Standard	V 2.4
■ Conformity Class	B
■ Netload Class	III
■ Realtime Klasse:	1
EtherNet/IP	
■ EtherNet/IP	yes

## Managed Switch PROmesh B8 compact

### Technical details

Diagnosis	
Functions	
<ul style="list-style-type: none"> <li>Port statistics:</li> </ul>	Errors Discards Neighborhood Netload
<ul style="list-style-type: none"> <li>Port Mirroring</li> </ul>	Incoming or incoming and outgoing packets Multiple source ports possible
Alerting	
<ul style="list-style-type: none"> <li>Trigger</li> </ul>	Port (Down, Status Change), Neighborhood Supply voltage, MRP
<ul style="list-style-type: none"> <li>Receiver</li> </ul>	PROFINET, SNMP
Security	
<ul style="list-style-type: none"> <li>Security</li> </ul>	User accounts (individual login) Port Alarm
Standards, guidelines, approvals	
EMC	
<ul style="list-style-type: none"> <li>Directive</li> </ul>	2014/30/EU
<ul style="list-style-type: none"> <li>Interference emission</li> </ul>	EN 55032
<ul style="list-style-type: none"> <li>Noise immunity</li> </ul>	EN 61000-6-2
Mechanical stability	
<ul style="list-style-type: none"> <li>Vibration</li> </ul>	IEC 60068-2-6
<ul style="list-style-type: none"> <li>Shock</li> </ul>	IEC 60068-2-27
<ul style="list-style-type: none"> <li>Free Fall</li> </ul>	IEC 60068-2-32
Approval	
<ul style="list-style-type: none"> <li>Europe</li> </ul>	CE
<ul style="list-style-type: none"> <li>USA</li> </ul>	UL
<ul style="list-style-type: none"> <li>Canada</li> </ul>	CSA
Environment	
<ul style="list-style-type: none"> <li>RoHS</li> </ul>	2011/65/EU
<ul style="list-style-type: none"> <li>REACH</li> </ul>	1907/2006/EG