

Product Datasheet - Technical Specifications



More information in our Web-Shop at > www.meilhaus.com and in our download section.

Your contact

Technical and commercial sales, price information, quotations, demo/test equipment, consulting:

| Tel.: | +49 - 81 41 - 52 71-0 | |
|---------|-------------------------|--|
| FAX: | +49 - 81 41 - 52 71-129 | |
| E-Mail: | il: sales@meilhaus.com | |
| Downlo | oads: | |

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbHTel.Am Sonnenlicht 2Fax82239 Alling/GermanyE-Mat

 Tel.
 +49 - 81 41 - 52 71-0

 Fax
 +49 - 81 41 - 52 71-129

 E-Mail
 sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted. © Meilhaus Electronic.

www.meilhaus.de

brainboxes







RoHS Compliant

PCIe 1xRS422/485 1MBaud Opto Isolated

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"

PX-387/PX-376




Features

- 1 port RS422/485
- PCI Express x1, x4, x8 x16 lane slots socket size
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



PX-387. PCIe 1xRS422/485 1MBaud Opto Isolated





Description

PCI Express Card providing one opto isolated RS422/485 serial port. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmitand 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 2000, XP, Server 2003, Vista, Server 2008, Windows 7 and Windows 8.

ISO 1400

PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows Server 2003 32 bit 64 bit Editions
- Windows XP 32 bit 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.





| ORDER | |
|--|--|
| Description | |
| PCIe 1xRS422/485 1MBaud Opto Isolated | |
| LP PCIe 1xRS422/485 1MBaud Opto Isolated | |

| Code |
|--------|
| PX-387 |
| PX-376 |



PX-387/PX-376



PCIe 1xRS422/485 1MBaud Opto Isolated

PX-387/PX-376: Full Specification

| Port | Ports | 1 x RS422/485 |
|---|---------------------|--|
| Pin 1 TXD- RS422/485 Pinout (9 Pin) | Connector | DB9 Connector - 9 Pin Male |
| Pin 2 TXD+ Pin 3 RTS- | FIFO size | 128 RX FIFO + 128 TX FIFO |
| Pin 4 RTS+ Pin 5 GND Pin 6 RXD- | Operating Distance | RS422/485 Standard 4000 ft : 1200 metres |
| Pin 7 RXD+ Pin 8 CTS Pin 6 Pin 9 Pin 9 CTS+ Pin 6 Pin 9 | Cable | No Cable; Integrated Connector |
| Port Settings | Baud Rate | 921,600 |
| 921,600 | Data Bits | 5,6,7 or 8 |
| >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>> | Parity | Odd, Even, None, Mark or Space |
| baud | Stop Bits | 1, 1.5 or 2 |
| | Flow Control | RTS/CTS, DSR/DTR, XON/XOFF |
| | Tx/Rx Modes | Full Duplex, Half Duplex Autogating |
| Interface | OS Compatibility | Microsoft Windows 8 32 bit 64 bit Editions |
| [Part 1733-] R5422(485 Pison (9 Pin) | | Microsoft Windows 7 32 bit 64 bit Editions |
| | | Windows Server 2008 32 bit 64 bit Editions Windows Vista 32 bit 64 bit Editions |
| Pic 2 (2025) Pic 6 Pic 9 Pic 9 (725) Pic 6 Pic 9 | | Windows Vista 32 bit 64 bit Editions |
| | BUS | PCI Express x1, x4, x8 x16 lane slots |
| Approvals | Other Approvals | AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS EMC: CE TAA |
| | Microsoft Approvals | Windows Server 2008 32 bit 64 bit editions |
| | | Windows Vista 32 bit 64 bit editions |
| | | Windows Server 2003 32 bit 64 bit editions Windows XP 32 bit 64 bit editions |
| | | |
| General | PCB Layers | 4 |
| | Power Consumption | 320mA @ 3.3V, 70mA @ 12V |
| | Weight | 0.07 kg |
| | Size | 162l x 18w x 120h mm |
| Box Content | Packaging | Installation CD including manual, Microsoft signed drivers & utilities |
| | Card | PCIe 1xRS422/485 1MBaud Opto Isolated |
| | | No Cable; Integrated Connector |
| Product Support | Warranty | Lifetime (online registration required) |
| | Support | Lifetime Web, Email and Phone Support from fully qualified, friendly |
| | | staff who work in and alongside the Product Development Team |
| Additional | OEM option | Available for bulk buy OEM |
| | Made In | Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year" |
| WINNER Manufacturer of the Year Made in the UK | Customisable | Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. |

Other PCI Express Cards: 1 Port RS232 | 2 Port RS232 | 4 Port RS232 | 8 Port RS232 | 1 Port RS422/485 | 2 Port RS422/485 | 4 Port RS422/485 Other Brainboxes Ranges: PCI | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial