

Product Datasheet - Technical Specifications



More information in our Web-Shop at ▶ www.meilhaus.com

Your contact

Technical and commercial sales, price information, quotations, demo/test equipment, consulting:

Tel.: +49 - (0)81 41 - 52 71-0

FAX: +49 - (0)81 41 - 52 71-129

E-Mail: sales@meilhaus.com













RoHS Compliant



PX-701/PX-260

PCIe 4xRS232 1MBaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 4 port RS232
- PCI Express x1, x4, x8 x16 lane slots socket
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



PX-701: PCIe 4xRS232 1MBaud

PX-260: LP PCIe 4xRS232 1MBaud



Description

PCI Express Card providing four RS232 serial ports. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 2000, XP, Server 2003, Vista, Server 2008, Windows 7 and Windows 8.

PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows Server 2003 32 bit 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.







ORDER
Description
PCle 4xRS232 1MBaud
LP PCIe 4xRS232 1MBauc

Code PX-701 PX-260

PX-701/PX-260



PCle 4xRS232 1MBaud

PX-701/PX-260: Full Specification

PA-701/PA-200. Full Specification			
Port	Ports	4 x RS232	
Pin 1 DCD RS232 Pinout (9 Pin Male)	Connector	DB9 Connector - 9 Pin Male	
Pin 2 RXD Pin 3 TXD Pin 4 PXP	FIFO size	128 RX FIFO + 128 TX FIFO	
Pin 4 DTR Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard	
Pin 7 RTS Pin 8 CTS Pin 6 Pin 9	Cable	4 port cable 44 way D to 4x9 Pin	
Pin 9 RI			
Port Settings	Baud Rate	921,600	
921,600	Data Bits	5,6,7 or 8	
> >> >	Parity	Odd, Even, None, Mark or Space	
baud	Stop Bits	1, 1.5 or 2	
	Flow Control	RTS/CTS, DSR/DTR, XON/XOFF	
	Tx/Rx Modes	Point to Point	
Interface	OS Compatibility	Microsoft Windows 8 32 bit 64 bit Editions Microsoft Windows 7 32 bit 64 bit Editions	
Pin 1 DCD RS232 Pinout (9 Pin Male) Pin 2 GAD Pin 1 Pin 5		Windows Server 2008 32 bit 64 bit Editions	
Fig. 4 1072		Windows Vista 32 bit 64 bit Editions	
Fin 9 22.		Windows Server 2003 32 bit 64 bit Editions	
	BUS	PCI Express x1, x4, x8 x16 lane slots	
Approvals	Other Approvals	AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS EMC: CE TAA	
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions	
		Windows Server 2008 32 bit 64 bit editions Windows Vista 32 bit 64 bit editions	
		Windows Vista 32 bit 64 bit editions Windows Server 2003 32 bit 64 bit editions	
		Windows XP 32 bit 64 bit editions	
General	PCB Layers	4	
	Power Consumption	380mA @ 3.3V	
	Weight	0.055 kg	
	Size	97l x 18w x 120h mm	
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities	
	Card	PCIe 4xRS232 1MBaud	
		4 port cable 44 way D to 4x9 Pin	
Product Support	Warranty	Lifetime (online registration required)	
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly	
The state of the s		staff who work in and alongside the Product Development Team	
Additional	OEM option	Available for bulk buy OEM	
***	Made In	Manufactured in the UK by Brainboxes Winner 2005 European	
Elektra O5 European Electronics Industry Awards		Electronics Industry Awards "Manufacturer of the Year"	
WINNER Manufacturer of the Year			
Made in the UK			