

## **Product Datasheet - Technical Specifications**



More information in our Web-Shop at **www.meilhaus.com** and in our download section.

#### Your contact

Technical and commercial sales, price information, quotations, demo/test equipment, consulting:

Tel.: +49 - 81 41 - 52 71-0

FAX: +49 - 81 41 - 52 71-129

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH | Am Sonnenlicht 2 82239 Alling/Germany

 Tel.
 +49 - 81 41 - 52 71-0

 Fax
 +49 - 81 41 - 52 71-129

 E-Mail
 sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.













## RoHS Compliant



## PX-805/PX-801

### PCIe 2xRS232 POS 1A SATA

### "SFRIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



#### **Features**

- 2 port RS232
- PCI Express x1, x4, x8 x16 lane slots socket
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### **Options**



PX-805: PCIe 2xRS232 POS 1A

PX-801: LP PCIe 1+1xRS232 POS 1A SATA



#### Description

PCI Express Card providing two powered RS232 serial ports. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC. Up to 1 Amp selectable power provided through pins 1 and 9 to attached peripherals. The extra power necessary is supplied to the PCI express card directly from the PC power supply unit through a Serial ATA SATA power connector: a neat, clean and green solution. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 2000, XP, Server 2003, Vista, Server 2008, Windows 7 and Windows 8.


PCI Express is the latest standard in PC connectivity.

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows Server 2003 32 bit 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.







ORDER
Description
PCIe 2xRS232 POS 1A SATA
LP PCIe 1+1xRS232 POS 1A SATA

Code PX-805 PX-801

PX-805/PX-801



# PCle 2xRS232 POS 1A SATA

PX-805/PX-801: Full Specification

- TX-003/TX-00T. Tuli Specific		2 pc222
Port	Ports	2 x RS232
Pin 1         DCD/12V/GND           Pin 2         RXD           Pin 3         TXD           Pin 4         DTR           Pin 5         GND           Pin 6         DSR           Pin 7         RTS           Pin 8         CTS           Pin 9         RI/12V/5V   Powered RS232 Pin out (9 Pin Male) Pin 1 Pin 5 Pin 5 Pin 5 Pin 6 Pin 9	Connector	DB9 Connector - 9 Pin Male
	FIFO size	128 RX FIFO + 128 TX FIFO
	Operating Distance	EIA - RS232 Standard
	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	921,600
921,600 >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Data Bits	5,6,7 or 8
	Parity	Odd, Even, None, Mark or Space
	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS, DSR/DTR, XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions
Inc. LOWING POWER BS U		Windows Server 2008 32 bit 64 bit Editions
Carl   Carl		Windows Vista 32 bit 64 bit Editions Windows Server 2003 32 bit 64 bit Editions
		Windows XP 32 bit 64 bit Editions
	BUS	PCI Express x1, x4, x8 x16 lane slots
Approvals	Other Approvals	AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS EMC: CE TAA
Αρριοναίδ	Microsoft Approvals	Windows 7 32 bit 64 bit Editions
	Timerosore / (pprovais	Windows Server 2008 32 bit 64 bit editions
		Windows Vista 32 bit 64 bit editions
		Windows Server 2003 32 bit 64 bit editions Windows XP 32 bit 64 bit editions
General	PCB Layers	4
	Power Consumption	400mA @ 3.3V
	Weight	0.064 kg
	Size	120l x 125w x 20h mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCIe 2xRS232 POS 1A SATA
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5 European Electronica Industry James	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users.