

Product Datasheet - Technical Specifications



More information in our Web-Shop at **• www.meilhaus.com**

Your contact

Technical and commercial sales, price information, quotations, demo/test equipment, consulting:

Tel.: +49 - (0)81 41 - 52 71-0

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH Am Sonnenlicht 2

 Am Sonnenlicht 2
 Tel. +49 - (0)81 41 - 52 71-0 E

 82239 Alling/Germany
 Mail sales@meilhaus.com

 Mentioned company and product names may be registered trademarks of the respective

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

www.meilhaus.com

Icron USB 3-2-1 Raven[™] 3104

4-Port USB 3.1, 100m CAT 6a/7 Point-to-Point Extender System

Industry's First USB 3-2-1 Extender Over Category Cable

The Icron USB 3-2-1 Raven 3104 provides the ability to connect all USB 3.1 Gen 1 (5Gbps) device types and is backwards compatible to USB 2.0 and 1.1 across a point-to-point connection up to 100m over CAT 6a/7. The Raven 3104 also includes an Ethernet pass-through for connecting to network enabled devices or to use existing infrastructure without losing LAN connectivity.



Summary of Features

- USB 3.1 Gen 1 data rate up to 5Gbps
- Supports all USB 3.1, 2.0, 1.1 devices simultaneously at full bandwidth; although if Isochronous support is required, use Raven 3104 Pro
- Four available 3.1 Gen 1 ports
- 100/1000 Ethernet channel; LAN pass-through
- Single cable, CAT 6a/7 up to 100m
- Point-to-point connection
- FCC and CE (Class B) compliant

Includes the ExtremeUSB-C[™] suite of features:

- Transparent USB extension supporting USB 3, 2 and 1
- True plug and play; no software drivers required
- Works with all major operating systems: Windows®, macOS[™], Linux[®] and Chrome OS[™]

Applications

- Remote Storage
- Security and Monitoring
- Video Matrix Systems
- Conformation Compre
- Conferencing Cameras





Specifications subject to change without notification. ©2022 Icron | An Analog Devices Brand #90-01599-D01

Icron USB 3-2-1 Raven 3104 Specifications

| LEX (LOCAL EXTENDER) MECHANICAL DATA | | REX (REMOTE EXTENDER) MECHANICAL DATA |
|---|------------------------|--|
| 137.3mm x 232.1mm x 33.0mm (5.4" x 9.1" x 1.3") | | 137.3mm x 232.1mm x 33.0mm (5.4" x 9.1" x 1.3") |
| 1x USB 3.1 B Receptacle | | 4x USB 3.1 A Receptacles |
| 1x RJ45 Ethernet 100/1000 Port | | 1x RJ45 Ethernet 100/1000 Port |
| 1x RJ45 Ethernet Link Port | | 1x RJ45 Ethernet Link Port |
| 24V 1A DC Locking Jack | | 24V 2.71A DC Locking Jack |
| 920g (2.03 lbs.) | | 990g (2.18 lbs.) |
| PACKAGE CONTENTS | | |
| 1x LEX (Local Extender) | | |
| 1x REX (Remote Extender) | | |
| 1x USB 3.1 Gen 1 Cable | | |
| 2x International Locking AC Adapters | | |
| 2x Country Specific Power Cords | | |
| 1x Quick Start Guide | | |
| Packaged weight: 2.91kg (6.4 | 12 lbs.) | |
| RANGE | | |
| Point-to-Point: | Up to 100m over C | AT 6a/7 |
| USB SUPPORT | | |
| USB Speeds: | SuperSpeed 5 Gbp | os, High-Speed, Full-Speed, Low-Speed |
| USB Bandwidth: | Up to 5Gbps | |
| Device Compatibility: | All Device Types a | nd Classes (Control, Interrupt, and Bulk) |
| Host Compatibility: | OHCI, UHCI, EHCI, xHCI | |
| Available Current at REX: | 1.2A (6W) per USB port | |
| Max Number of USB Devices | : 30 | |
| ENVIRONMENTAL | | |
| Temperature: | 0°C – 50°C (32°F – | 122°F) Operating, -20°C – 70°C (-4°F – 158°F) Storag |
| Humidity: | 20-80% Operating | , 10-90% Storage Relative Humidity Non-Condensing |
| COMPLIANCE | | |
| Certifications: | FCC (Class B), CE (C | lass B), RoHS2/3 (CE), ICES-003 Issue 7, EN 62368-1 |
| SUPPORT | | |
| Warranty: | 2 years | |

Ordering Information

The Icron USB 3-2-1 Raven[™] 3104 system includes a LEX, REX, USB 3.1 Gen 1 cable, two international power adapters with country specific power cords, Quick Start Guide and two-year warranty.

| PART # | NAME | DESCRIPTION |
|----------|---------------------------------|--|
| 00-00421 | lcron USB 3-2-1 Raven 3104 - NA | 4-Port USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - NA |
| 00-00422 | lcron USB 3-2-1 Raven 3104 - EU | 4-Port USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - EU |
| 00-00423 | lcron USB 3-2-1 Raven 3104 - UK | 4-Port USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - UK |
| 00-00424 | lcron USB 3-2-1 Raven 3104 - AU | 4-Port USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - AU |
| 00-00425 | lcron USB 3-2-1 Raven 3104 - JP | 4-Port USB 3-2-1 100m CAT 6a/7 PTP Extender System, Silver, 100-240V Power Adapters - JP |
| 10-00620 | Raven Silver Mounting Kit | Raven/Maverick Silver Mounting Kit, Set of 2 Mounting Brackets, Bolts included |