

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

**Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:**

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - 81 41 - 52 71-0**
Fax **+49 - 81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.

www.meilhaus.de

EATON Sefelec RCP2A Accessories List	
RCP2A	Portable milliohm-meter 0.1A, 1A and 10A with battery and charger
RCP2 Accessories	
TE28/1	Milliohm-meter - 3m cable with remote control button on the bipolar tip test probe; 4 pins Jaegger connector to the RCP2A
CO10	Milliohm-meter - 12m cable end with large crocodile clip; 3 pins Jaegger connector to the RCP2A
TE9/1	Milliohm-meter - 3m cable bipolar tips test probe (small model); 4 pins Jaegger connector to the RCP2A
TE9/IE	Milliohm-meter - 3m cable bipolar tips test probe (small model); 3 pins Jaegger connector to the RCP2A
CO8	Milliohm-meter - 12m cable end with small sized kelvin clip; 3 pins Jaegger connector to the RCP2A
CO9	Milliohm-meter - 20m extension cable; 3 pins Jaegger connector to the RCP2A/3 pins Jaegger connector to the accessory
CO179A	Cable for RCP2APRO
CO250	Milliohm-meter - 2.5m - 4-wire lead with banana plugs and tips (VN-VG) for RCP2A
CO251	2-wire probe, 4 pins male plug, concentric tips, length=150mm, for RCP2A
CO255	2-wire lead, 3 pins male plug, Kelvin crocodile clip for RCP2A
CO258	2-wire probe, 4 pins male plug, concentric tips, length=180mm, for RCP2A
CO262	Cable for remote control display
RCP2A Options	
RCP-01	Remote control display; includes 1 CO262 connexion cable of 3m
RCP-02	Additional battery pack
RCP-03	Additional battery charger: Input 100...240V, 50/60Hz, directly plugged into the wall
RCP-04	12m extension cable for remote control display and the main measurement lead
RCP-05	Storage suitcase
RCP-06	15m extension cable on reel
RCP-07	90m extension cable on reel
RCP-08	RCU/PC adaptor with power supply - cable for direct communication between PC and remote control display
RCP-09	RCP2APRO software + CO179A PC connection cable
RCP-10	20m extension cable with male/male plug
RCP-11	20m extension cable with male/female
RCP-13	Additional battery charger: Input 100...240V, 50/60Hz, with power cord to plug to the mains (this is not the charger which is plugged directly into the wall)
RCP-14	Adaptation cable from Jaeger 3 pins male connector to 4 pins female connector; 0.3m
RCP-14-XX	Adaptation cable from Jaeger 3 pins male connector to 4 pins female connector; up to 15m. Please select length
RCP-15	Protection lid
RCP-17	1mΩ class 0.5% verification shunt resistor
RCP-18	5mΩ class 0.5% verification shunt resistor
RCP-19	10mΩ class 0.5% verification shunt resistor
RCP-20	50mΩ class 0.5% verification shunt resistor
RCP-21	USB - serial DB9 bi-direction converter
RCP-24	Bag for RCP2A accessories - replaces RCP-16
RCP2A Calibration kit	
RCP-91	Calibration box for RCP2A; included in this reference: CO264 lead which connects the calibration box to the RCP2A (has to be ordered with ISO17025 certificate)