

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH | Tel. **+49 - 81 41 - 52 71-0**
Am Sonnenlicht 2 | Fax **+49 - 81 41 - 52 71-129**
82239 Alling/Germany | E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.

www.meilhaus.de

EATON Sefelec1000M Accessories List	
SEFELEC1000M	Megohmmeter 1000V/200GΩ
SEFELEC1000M Accessories	
SEFA-SE15	Insulation - sense cable end with a probe - 1.5m + Lemo connector; equivalent to TE17
SEFA-SE15-05	Insulation - sense cable end with a probe - 5m + Lemo connector; equivalent to TE17
SEFA-SE15-10	Insulation - sense cable end with a probe - 10m + Lemo connector; equivalent to TE17
SEFA-CO175-02	Return lead 4mm HV/insulation length; 2m
SEFA-CO175-05	Return lead 4mm HV/insulation length; 5m
SEFA-CO0175-10	Return lead 4mm HV/insulation length; 10m
SEFA-FTHV10-02	4mm plug cable HV/insulation length; 2m (no probe)
SEFA-FTHV10-05	4mm plug cable HV/insulation length; 5m (no probe)
SEFA-FTHV10-10	4mm plug cable HV/insulation length; 10m (no probe)
SEFA-AO10	Dual palm remote switch - cable 2m
SEFA-AD5X-M10	MXS to SEFELEC1000-M HV connections external adaptor
SEFA-CO160	SEFELEC series green/red safety lamp
SEFA-KR	SEFELEC series 19" rack mounting adaptors
SEFA-AD15	Set of 2 adaptors for old TE17/CO19 to fit with SEFELEC1500M
SEFELEC1000M Options	
SEFO-IEEE488	SEFELEC series IEEE488.2/GPIB interface
SEFO-5XREAR	Rear connections for SEFELEC 5x series
SEFO-5XRC	5X remote controls connectors module
SEFO-5X2TO	SEFELEC series green/red safety lamp
SYWinpass-MX	Winpass MX software. Works with Ethernet, RS232, or GPIB interface. For Windows 7 32/64 bits and Windows 10 (English, French, German, Russian)
SEFELEC1000M Calibration kit	
BEM24	Metal box including 23 standard resistors from 5kΩ to 100TΩ (500V max, accuracy 1%) + temperature measurement and humidity indicator - this box allows to verify the SEFELEC1500M calibration. Included : 5, 10, 50, 100, and 500kΩ, 1, 4, 5, 5, 10, 20, 50, 100, and 500 MΩ, 1, 5, 10, 50, 100, and 500GΩ, 1, 5, 10, and 100TΩ; to be ordered with SEFA-SE15 + SEFA-HV15 (interconnexion leads) We recommend to order the BEM24 with ISO17025 certificate