

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH | Tel. **+49 - 81 41 - 52 71-0**
Am Sonnenlicht 2 | Fax **+49 - 81 41 - 52 71-129**
82239 Alling/Germany | E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.

www.meilhaus.de

EATON Sefelec1500M Accessories List

SEFELEC1500M	Pico-Amperemeter/Tera-Ohmmeter 1500V/2000TΩ
SEFELEC1500M Accessories	
SEFA-SE15	Insulation - sense cable end with a probe - 1.5m + Lemo connector; replaces TE17
SEFA-HV15	Insulation - high voltage cable end with 4mm plug - 1.5m + Lemo connector; replaces CO19
SEFA-HVSE15-10	Insulation: Set of 2x 10m length cable, one end with Lemo connectors (HV or SE), the other ends are free cable for hardwire connections to test bench
SEFA-RE15	Insulation: Set of 2 cables to connect REMA standard resistor to the megohm-meter - 0.5m; replaces CO58
SEFA-AD5X-M15	M1501M/U/P to SEFELEC1500-M HV connections external adaptor
SEFA-KR	SEFELEC series 19" rack mounting adaptors
SEFA-AO10	Dual palm remote switch - cable 2m
SEFA-1500MHRT	Humidity and temperature measurement probe for SEFELEC Series/USB
SEFA-SRE24	Insulation - guard ring measurement electrode for surface/volumic measurement
SEFA-AD15	Set of 2 adaptors for old TE17/CO19 to fit with SEFELEC1500M
SEFELEC1500M Options	
SEFO-IEEE488	SEFELEC series IEEE488.2/GPIB interface
SEFO-1500MREAR	Rear connections for SEFELEC1500M
SEFO-C0160	SEFELEC series green/red safety lamp
SEFO-BAPA	Protection interface for megohm-meter SEFELEC1500M when using an external power supply to get more than 1500VDC; can be used up to 10kVDC without RLHT. Delivered with cables to connect to SEFELEC1500M & DUT/device under test
RLHT 50-3K	11kV up to 50kV protection resistance for BAPA
RLHT 70-6K	11kV up to 7 kV protection resistance for BAPA
SYWinpass-MX	Winpass MX software. Works with Ethernet, RS232, or GPIB interface. For Windows 7 32/64 bit and Windows 10 (English, French, German, Russian)
SEFELEC1500M Calibration kit	
BEM24	Metal box including 23 standard resistors from 5kΩ to 100TΩ (500V max, accuracy 1%) + temperature measurement and humidity indicator - this box allows to verify the SEFELEC1500M calibration. Included : 5, 10, 50, 100, and 500kΩ, 1, 4,5, 5, 10, 20, 50, 100, and 500 MΩ, 1, 5, 10, 50, 100, and 500GΩ, 1, 5, 10, and 100TΩ; to be ordered with SEFA-SE15 + SEFA-HV15 (interconnexion leads). We recommend to order the BEM24 with ISO17025 certificate