

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

FAX: **+49 - (0)81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0**
Fax **+49 - (0)81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

Network cables tester (RJ-45, RJ-11)

Characteristics

- Designed for RJ45/RJ11 modular cables, 10/100 base-T cable and Token Ring cable
- The Lan cable tester can verify cable continuity, open, short circuit and miss-wired.
- The deported receiving module is available for installed cables far away either on the wall plates or on the patch panels.
- Automatic or manual sweep mode
- Display: LED indication for wire status.
- Buzzer sound warning for wire status.
- EN61326-1
- Supplied with carrying case



SEFRAM 95

Specifications	SEFRAM 95
Types of tests	cable continuity (shielded cable included), open, short circuit and miss-wired.
Test modes	Automatic and manual
Buzzer	Sound when continuity absence
Deported module	For installed cables
Main specifications	
Display	LED
Operating Temperature	0°C to 40°C
Storage temperature	-10°C to 40°C (battery removed)
Alimentation	9V (6F22,006P) battery x1
Dimensions	132 x 55 x 39mm (main unit) 74 x 30 x 25mm (deported module)
Weight	148g (main unit) 33g (deported module)
Warranty	1 year

Supplied with: test cables, user's guide, battery



Carring case



FTSEFRAM95 A 00 - Specifications can be updated without notice

