

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

FAX: **+49 - (0)81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0**
Fax **+49 - (0)81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

Sefram

SEFRAM9891 Refrigerant Leak Detector

■ Features :

Air Sucking System for faster response and higher sensitivity. Refrigerant leakage detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and refrigerant.

This unit used newly developed semiconductor sensor which is extremely sensitive to variety of general used refrigerant. Microprocessor control with advanced digital signal processing.

■ Specifications :

- Heated semiconductor gas sensor
- 3 level sensitivity
- 7 LED Tri-colored leak level indicator
- Variable intensity audible alarm
- Ambient concentration reset
- 15.5" (40cm) flexible probe
- Detection of R-22, R-32, R-290, R-131a, R-404A, R-410A, R-407C, R-502, R-600A, R-1234yf... Refrigerants Gas
- Sensibility : 3g/year
- Low battery indication
- Battery life : approximately 12 hours normal use (alkaline battery)
- Reference leak source included
- Hard carrying case included
- Warm-up time: 45 seconds
- Operating temperature: 0 to 40 °C (32 to 104°F)
- Dimensions : L.22,1 x W.7,4 x H.4,7 cm
- Weight : 421g (with batteries)
- Power Source : 4 AA Size alkaline batteries



Sefram



Follow us on :



FT SEFRAM9891 A00 - Specifications can be updated without notice

Visit our website: www.sefram.com