

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

FAX: **+49 - (0)81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0**
Fax **+49 - (0)81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

SEFRAM9892 Combustible Gas Detector

■ Features :

Combustible Gas Leak Detector is extremely useful as a general purpose tool in any environment where gasoline, propane, natural gas or fuel oil is used. This unit uses a newly developed semiconductor sensor which is extremely sensitive to variety of general used combustible.

■ Specifications :

- Microprocessor control with advanced digital signal processing
- Multi color visual display
- High-Low leak sensitivity selector
- Detection of detectable gases : Gasoline, propane, natural gas or fuel oil
- Sensitivity : variable, as low as 5ppm
- Low battery indication
- Semiconductor gas sensor
- Reference Leak Source included
- Manual ambient concentration reset
- 15.5" (40 cm) flexible stainless probe
- Warm-up time: 90 Seconds
- Battery life : Approximately 40 hours normal use (alkaline battery)
- Operating temperature : -10 to 40°C(14 to 104°F)
- Power source: 4 AA size alkaline batteries
- Dimensions: L22.1 x W7.4 x H4.7 cm
- Weight: 421g (with batteries)

■ Applications

- Detect leaks in automobile exhaust and fuel system
- Detect leaks in liquid or gas fired heating systems
- Safety checks at propane filling stations
- Search for arson residue (detects accelerants)
- Detect fuel in marine bilges
- Check manholes/sewers for safety
- Check for cracked heat exchangers
- Detect solvent residue

