

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

FAX: **+49 - (0)81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0**
Fax **+49 - (0)81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

10W N RF ATTENUATOR SET

The TBAS3 RF attenuator set consists of 3dB, 6dB, 10dB and 20dB 10W N attenuators in a beech wood box.



1 Specification

Tolerance: 3, 6, 10 dB +/- 0.5 dB
20 dB +/- 0.8 dB

Frequency range: DC-3GHz, VSWR < 1.2

Power rating: 10W @ -55 to 70°C; up to 125°C with 50% power de-rating

Connectors: N-male / N-female; bidirectional

Dimensions: 150mm x 95mm x 45mm


Weight: 505g

10W N RF ATTENUATOR SET

2 Ordering Information


Part Number	Description
TBAS3	Attenuator set 3dB, 6dB, 10dB, 20dB, 3GHz, 10W, N

3 Sample Plots




3dB Attenuator, S₂₁

10W N RF ATTENUATOR SET




6dB Attenuator, S₂₁

10W N RF ATTENUATOR SET



10dB Attenuator, S21

10W N RF ATTENUATOR SET



20dB Attenuator, S₂₁