

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0** E-
Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

www.meilhaus.com

N-Female VNA calibration kit, 6 GHz

1 Introduction

The TBVC-NF6 is a calibration kit for Vector Network Analyzers. It contains an Open, a Short, a Load and a Through. It is used for OSLT calibration in the frequency range DC - 6 GHz.



Picture 1: TBVC-NF6

2 Specification

Load:

N-Female
 $Z = 50 \Omega$
Return loss > 35 dB

THROUGH:

N-Female
 $Z = 50 \Omega$
Loss = 2 GΩ/s
Delay = 80.375 ps

Short:

N-Female
 $Z = 50 \Omega$
Delay = 0 ps
Loss = 2.88 GΩ/s
 $L_0 = 1.19 \text{ pH}$
 $L_1 = -8.9\text{e-}22 \text{ H/Hz}$
 $L_2 = 1.4\text{e-}31 \text{ H/Hz}^2$
 $L_3 = 1.6\text{e-}42 \text{ H/Hz}^3$

Open:

N-Female
 $Z = 50 \Omega$
Delay = 6.810 ps
Loss = 979.28 GΩ/s
 $C_0 = 4.96 \text{ fF}$
 $C_1 = -2.274\text{e-}24 \text{ fF/Hz}$
 $C_2 = 8.78\text{e-}35 \text{ fF/Hz}^2$
 $C_3 = 5.54\text{e-}45 \text{ fF/Hz}^3$

Frequency range: DC – 6 GHz
Box dimensions: 145 mm x 145 mm x 55 mm
Weight: 475 g

N-Female VNA calibration kit, 6 GHz

The calibration kit file is pre-installed with our TBVNA-6000 software and can be downloaded separately from our website.

3 Ordering Information

Part Number	Description
TBVC-NF6	N-female OSLT VNA calibration kit, 6 GHz

4 History

Version	Date	Author	Changes
V 1.0	2.5.2025	Mayerhofer	Creation