

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - (0)81 41 - 52 71-0**

FAX: **+49 - (0)81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel. **+49 - (0)81 41 - 52 71-0**
Fax **+49 - (0)81 41 - 52 71-129**
E-Mail sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Errors and omissions excepted. © Meilhaus Electronic.

Component Parameter Test Instruments

A. TH2851 Series Impedance Analyzer

Features

- Test frequency: 10Hz-130MHz
- High precision: using automatic balance bridge technology, four-terminal pair test configuration
- High stability and consistency
- High speed: the fastest test speed up to 5ms
- High resolution: 10.1-inch capacitive touch screen, resolution 1280*800
- Three test methods: point test, list scan, and graph scan
- 1601 point multi-parameter list scanning function
- Four-parameter measurement
- 4-channel graphic scanning function, each channel can display 4 curves, 16 kinds of split-screen display modes for channels and curves
- Powerful sorting: 10 grades sorting in LCR mode
- Graphic scanning mode, each curve is sorted individually
- High compatibility: Support SCPI instruction set, compatible with KEYSIGHT E4990A, E4980A, E4980AL, HP4284A

Applications

- **Passive component:**
Impedance parameter estimation and performance analysis of capacitor, inductor, magnetic core, resistor, piezoelectric devices, transformers, chip components and network components
- **Semiconductor component**
Parasitic parameter test and analysis of LED driver integrated circuit
C-VDC features of varactors
Parasitic parameter analysis of transistors or integrated circuit
- **Other components**
Impedance assessment of printed circuit boards, relays, switches, cables, batteries

Specifications

Model	TH2851-015	TH2851-030	TH2851-050	TH2851-080	TH2851-130
Display	10.1 Inches TFT LCD Display 1280×RGB×800, Touch Screen				
AC Parameter	Cp/Cs、Lp/Ls、Rp/Rs、 Z 、 Y 、R、X、G、B、 θ 、D、Q、V _{AC} 、I _{AC}				
DC Parameter	V _{DC} 、I _{DC} 、DCR				
Test Frequency	Range	10Hz--15MHz	10Hz--30MHz	10Hz--50MHz	10Hz--80MHz
	Resolution	1mHz			
	Relative frequency tolerance	≤±0.0007%			
Test Level	AC Voltage	5mV—2Vrms			
	Resolution	1mV			
	AC Current	50uA—20mArms			
	Resolution	10uA			
DC Bias	Voltage	0V-±40V			
	Resolution	1mV			
	Current	0mA-±100mA			
	Resolution	40 μ A			
Test terminal configuration	Four Terminal Pair				
Output impedance	25 Ω / 100 Ω				
Typical Test time (Speed)	Five Shift: 1(Fast)—5(Accuracy)				
	1: 2.5ms 2: 10ms 3: 40ms 4: 80ms 5: 400ms (Does not include the arithmetic average of the communication time, each frequency test speed will be slightly different)				
Max Accuracy	1kHz: 0.08%				
	1MHz: 0.08%				
	2MHz: 0.5%				
	10MHz: 1%				
	130MHz: 5.0%				



NEW

Standard	RS232	USB HOST	USB DEVICE	LAN
	HANDLER	GPIO	HDMI	VGA

Dimension: 428mm(W)x220mm(H)x325mm(D)
Weight: 14.5kg

- **Dielectric material**
Dielectric constant and loss angle evaluation of plastics, ceramics and other materials
- **Magnetic materials**
Magnetic permeability and loss angle assessment of ferrite, amorphous body and other magnetic materials
- **Semiconductor materials**
Dielectric constant, electrical conductivity and C-V characteristics of semiconductor materials
- **Liquid crystal cell**
Dielectric constant, elastic constant and C-V characteristics of liquid crystal cell

Component Parameter Test Instruments

A. TH2851 Series Impedance Analyzer

Test Range	E: 1×10^{18}	
Cs, Cp	-9.99999EF ~ +9.99999EF	
Ls, Lp	-9.99999EH ~ +9.99999EH	
D	-9.99999E ~ +9.99999E	
Q	-9.99999E ~ +9.99999E	
R, Rs, Rp, X, Z, R _{DC}	-9.99999E Ω ~ +9.99999E Ω	
G, B, Y	-9.99999ES ~ +9.99999ES	
Vdc	-9999V ~ +9999V	
Idc	-9999mA ~ +9999mA	
θ_r	-999999rad ~ +999999rad	
θ_d	-180.0deg ~ +180.0deg	
Δ %	-999999% ~ +999999%	
Multi-function parameter list scan	1601 points, each point can be set to average, and each point can be sorted separately Sweep parameters: measurement parameters, test frequency, AC voltage, AC current, DC BIAS voltage, DC BIAS current	
Graphic scan	parameter	Frequency, ACV, ACI, DCV, DCI
	Types	Logarithmic, linear, frequency segmentation
	Points	2-1601
	Number of channels	4
	Number of curves	4 Per Channel
Split Screen	14 (Channel and Curve)	
Equivalent circuit analysis	3-element model: 4, 4-element model: 3	
Sorting	10 levels of sorting in LCR mode; each curve in scan mode is sorted individually	
Interface	RS232C, USB HOST, USB DEVICE, LAN, GPIB, HANDLER, VGA, HDMI	
Power-on warm-up time	60 Minutes	
Input Voltage	100-120VAC/198-242VAC Option, 47-63Hz	
Power consumption	Max 150VA	
Measurement (WxHxD) mm ³	428x220x325	
Weight	14.5kg	

Standard accessories

Three core power cord

TH26010 Gold-plated short circuit board

TH26047 Test fixture

TH26005C Four-terminal test fixture