

Product Datasheet - Technical Specifications



More information in our Web-Shop at ► www.meilhaus.com and in our download section.

Your contact

Technical and commercial sales, price information,
quotations, demo/test equipment, consulting:

Tel.: **+49 - 81 41 - 52 71-0**

FAX: **+49 - 81 41 - 52 71-129**

E-Mail: sales@meilhaus.com

Downloads:

www.meilhaus.com/en/infos/download.htm

Meilhaus Electronic GmbH
Am Sonnenlicht 2
82239 Alling/Germany

Tel.	+49 - 81 41 - 52 71-0
Fax	+49 - 81 41 - 52 71-129
E-Mail	sales@meilhaus.com

Mentioned company and product names may be registered trademarks of the respective companies. Prices in Euro plus VAT. Errors and omissions excepted.
© Meilhaus Electronic.

www.meilhaus.de

These modules are converters from USB to serial COM. Use them to connect classic serial devices with RS232 to USB ports. The „commercial line“ models have robust, compact, economic plastic housings and can be used for mobile applications or in the office.

- Converter USB to 1x RS232.
- With or without LEDs.
- Rates up to 921.6 kbps.
- Send and receive FIFO.
- Compatible with USB 2.0 and 1.1.

USB-COM (Mini, DB9)



Model	Converter		Serial		Isolation	Size (mm)	Supply
	from	to	Ports	Rate (kbps)			
USB-COM Mini/ LEDs	USB 2.0	RS232/DB9	1	921,6	-	70 x 40 x 20	USB-powered
USB-COM Mini/ without LEDs	USB 2.0	RS232/DB9	1	921,6	-	70 x 40 x 20	USB-powered